











CAM-ALLOY CHAIN SLINGS — GRADE 80 WORKING LOAD LIMITS* (LBS.)

TRADE SIZE (INCHES)	SINGLE SLING TYPE S	DOUBLE SLINGS TYPE D			TRIPLE TYPE T AND QUADRUPLE TYPE Q SLINGS			TRADE SIZE (MM)
								
7/32	2100	3600	3000	2100	5500	4500	3200	5.5
9/32	3500	6100	4900	3500	9100	7400	5200	7
5/16	4500	7700	6300	4500	11700	9400	6700	8
3/8	7100	12300	10000	7100	18400	15100	10600	10
1/2	12000	20800	17000	12000	31200	25500	18000	13
5/8	18100	31300	25600	18100	47000	38400	27100	16
3/4	28300	49000	40000	28300	73500	60000	42400	20
7/8	34200	59200	48400	34200	88900	72500	51300	22
1	47700	82600	67400	47700	123900	101200	71500	25
1-1/4	72300	125200	102200	72300	187800	153400	108400	32

NOTE: 5/16" (8mm) through 7/8" (22mm) alloy manufactured to G100 specifications.



CARE AND PRECAUTIONS

• **Inspect Chain** regularly for elongation, excessive wear, bent links, damaged welds or spread hook openings. • **Clean Chain** regularly as dirt and grit can cause wear at link bearing points. When using Cam-Alloy chain slings where temperatures attain 600°F, consult Campbell Chain for reductions in Working Load Limits. • **Store Chains** in a clean dry area, preferably by hanging on walls or racks rather than placing chains on floors where they are subject to abuse.

*WARNING: DO NOT EXCEED WORKING LOAD LIMIT

• **DO NOT** bounce or jolt load when lowering or lifting. • **DO NOT** apply load to belted, knotted or linked chain. • **DO NOT** anneal alloy slings. Return sling to factory for proper treatment. • **DO NOT** lift from point of hook. • **DO NOT** drop load suddenly on chain or rest load on chain. • **DO NOT** expose chain to sharp edges of load; use pads. • **DO NOT** force or hammer hooks or chain into position. • **DO NOT** carry unbalanced loads.

CAMPBELL
CHAIN & FITTINGS

**100%
AMERICAN
STRONG**
FROM CHAIN TO HOOK

